



## Technical characteristics report

Serial: GRANADA

Size: All sizes

Norm: UNE-EN 14411

Group: Alb

Ceramic Tiles extruded for internal and external flooring and wall finishes, with water absorption Eb  $\leq$ 3%

### GRANADA

| Name, Test                                                  | European norm         | Value                               |
|-------------------------------------------------------------|-----------------------|-------------------------------------|
| Size, thickness, side straightness, flatness, orthogonality | USO 10545-02          | Amply meets the standard            |
| Water absorption capacity                                   | EN ISO 10545-03       | < 1,5%                              |
| Flexion resistance                                          | EN ISO 10545-04       | > 30 N/mm2                          |
| Resistance to the abrasion, method PEI                      | EN ISO 10545-07       | III: red<br>IV: white/ salmon/straw |
| Thermal shock resistance                                    | EN ISO 10545-9        | Guaranteed                          |
| Cracking resistance                                         | EN ISO 10545-11       | Guaranteed                          |
| Frost resistance                                            | EN ISO 10545-12       | Guaranteed                          |
| Resistance to acids                                         | EN ISO 10545-13       | GLA                                 |
| Resistance to alcalis                                       | EN ISO 10545-13       | GLA                                 |
| Resistance to cleaning products                             | EN ISO 10545-13       | GA                                  |
| Stains resistance                                           | EN ISO 10545-14       | 5                                   |
| Slip resistance (pendulum)                                  | UNE-ENV<br>12633:2003 | Class 2                             |
| Critical angle of slip (inclined platform)                  | DIN 51130             | R10                                 |

QUALITY DEPARTMENT